594-C-38 FEM 1.209:42175/

JAN 1 1 1990

FLOOD INSURANCE STUDY

TOWNSHIP OF CLIFTON, PENNSYLVANIA
LACKAWANNA COUNTY



FEBRUARY 2, 1990

Federal Emergency Management Agency

COMMUNITY NUMBER - 421751

NOTICE TO
FLOOD INSURANCE STUDY USERS

Communities participating in the National Flood Insurance Program (NFIP) have established repositories of flood hazard data for floodplain management and flood insurance purposes. This Flood Insurance Study (FIS) may not contain all data available within the repository. It is advisable to contact the community repository for any additional data.

Part or all of this FIS may be revised and republished at any time. In addition, part of this FIS may be revised by the Letter of Map Revision (LOMR) process, which does not involve republication or redistribution of the FIS. It is, therefore, the responsibility of the user to consult with community officials and to check the community repository to obtain the most current FIS components.

Initial Flood Insurance Study Effective Date: February 2, 1990

Flood Insurance Study Revised:

TABLE OF CONTENTS

		Page
1.0	INTRODUCTION	1
	1.1 Purpose of Study	1
	1.2 Authority and Acknowledgments	1
	1.3 Coordination	1
2.0	AREA STUDIED	2
	2.1 Scope of Study	2
	2.2 Community Description	2
	2.3 Principal Flood Problems	2
	2.4 Flood Protection Measures	2
3.0	ENGINEERING METHODS	2
	3.1 Hydrologic Analyses	4
	3.2 Hydraulic Analyses	4
4.0	FLOODPLAIN MANAGEMENT APPLICATIONS	5
	4.1 Floodplain Boundaries	5
	4.2 Floodways	6
5.0	INSURANCE APPLICATIONS	6
6.0	FLOOD INSURANCE RATE MAP	9
7.0	OTHER STUDIES	9
8.0	LOCATION OF DATA	9
9.0	BIBLIOGRAPHY AND REFERENCES	10

TABLE OF CONTENTS - continued

FIGURES

Figure 1 - Vicinity Map 3

Figure 2 - Floodway Schematic 7

TABLES

Table 1 - Summary of Discharges 4

EXHIBITS

Exhibit 1 - Flood Profiles
Lehigh River Panels 01P-03P
Meadow Brook Panel 04P

Exhibit 2 - Flood Insurance Rate Map Index and Street Index
Flood Insurance Rate Map

Exhibit 3 - Elevation Reference Marks

FLOOD INSURANCE STUDY
TOWNSHIP OF CLIFTON, LACKAWANNA COUNTY, PENNSYLVANIA

1.0 INTRODUCTION

1.1 Purpose of Study

This Flood Insurance Study investigates the existence and severity of flood hazards in the Township of Clifton, Lackawanna County, Pennsylvania, and aids in the administration of the National Flood Insurance Act of 1968 and the Flood Disaster Protection Act of 1973. This study has developed flood risk data for various areas of the community that will be used to establish actuarial flood insurance rates and assist the community in its efforts to promote sound floodplain management. Minimum floodplain management requirements for participation in the National Flood Insurance Program (NFIP) are set forth in the Code of Federal Regulations at 44 CFR, 60.3.

In some states or communities, floodplain management criteria or regulations may exist that are more restrictive or comprehensive than the minimum Federal requirements. In such cases, the more restrictive criteria take precedence and the state (or other jurisdictional agency) will be able to explain them.

1.2 Authority and Acknowledgments

The sources of authority for this Flood Insurance Study are the National Flood Insurance Act of 1968 and the Flood Disaster Protection Act of 1973.

The hydrologic and hydraulic analyses for this study were prepared by the U. S. Geological Survey (USGS) for the Federal Emergency Management Agency (FEMA), under Inter-Agency Agreement No. EMW-85-E-1823, Project Order No. 21. This work was completed in July 1987.

1.3 Coordination

On April 16, 1985, an initial Consultation and Coordination Officer's (CCO) meeting was held with representatives from FEMA, the township, and the USGS (the study contractor) to determine the streams to be studied by detailed methods.

On March 6, 1989, a final CCO meeting was held with representatives of FEMA, the township, and the study contractor to review the results of the study.

2.0 AREA STUDIED

2.1 Scope of Study

This Flood Insurance Study covers the incorporated area of the Township of Clifton, Lackawanna County, Pennsylvania. The area of study is shown on the Vicinity Map (Figure 1).

The following streams were studied by detailed methods: the Lehigh River, from the downstream corporate limits to a point approximately 1.9 miles upstream, and from a point approximately 0.7 mile downstream of the dam at West End Pond upstream to the dam at West End Pond; and Meadow Brook, from its confluence with Tamarack Creek to a point approximately 0.6 mile upstream. The areas studied by detailed methods were selected with priority given to all known flood hazard areas and areas of projected development and proposed construction through July 1992.

Ash Creek, Silver Creek, Tamarack Creek, West Fork, Larsen Lake, Big Bass Lake, several unnamed streams, and the remaining portions of the Lehigh River and Meadow Brook were studied by approximate methods. Approximate analyses were used to study those areas having a low development potential or minimal flood hazards. The scope and methods of study were proposed to, and agreed upon by, FEMA and the Township of Clifton.

2.2 Community Description

The Township of Clifton is located in the southern portion of Lackawanna County in eastern Pennsylvania, approximately 15 miles south of Scranton. It is bordered by the Township of Coolbaugh to the south, the Township of Lehigh to the southwest, the Township of Sterling to the east, and the Townships of Covington and Spring Brook to the north.

2.3 Principal Flood Problems

Major floods cause localized inundation of structures along the Lehigh River and Meadow Brook.

2.4 Flood Protection Measures

No flood control structures have been installed to alleviate flooding within the township.

3.0 ENGINEERING METHODS

For the flooding sources studied in detail in the community, standard hydrologic and hydraulic study methods were used to determine the flood hazard data required for this study. A flood event of a magnitude which is expected to be equaled or exceeded once on the average during any 100-year period (recurrence interval) has been selected as having special significance for floodplain management and for flood insurance rates.



FIGURE 1

FEDERAL EMERGENCY MANAGEMENT AGENCY

TOWNSHIP OF CLIFTON, PA

(LACKAWANNA CO.)

APPROXIMATE SCALE

4 0 4 8 12 MILES

VICINITY MAP

This event, commonly termed the 100-year flood, has a 1 percent chance of being equaled or exceeded during any year. Although the recurrence interval represents the long term average period between floods of a specific magnitude, rare floods could occur at short intervals or even within the same year. The risk of experiencing a rare flood increases when periods greater than 1 year are considered. For example, the risk of having a flood which equals or exceeds the 100-year flood (1 percent chance of annual exceedence) in any 50-year period is approximately 40 percent (4 in 10), and, for any 90-year period, the risk increases to approximately 60 percent (6 in 10). The analyses reported herein reflect flooding potentials based on conditions existing in the community at the time of completion of this study. Maps and flood elevations will be amended periodically to reflect future changes.

3.1 Hydrologic Analyses

Hydrologic analyses were carried out to establish the peak discharge-frequency relationships for each flooding source studied in detail affecting the community.

The flood-frequency discharge values for the Lehigh River and Meadow Brook were determined using data from the river gage at Stoddartsville (No. 01447500) and the methods outlined in USGS Bulletin 17B (Reference 1). Factors equal to drainage-area ratios raised to the 0.8 power were used to transfer discharge values thereby developed for the Flood Insurance Study for the Township of Lehigh to sites located within the Township of Clifton (Reference 2).

A summary of the drainage area-peak discharge relationships for the streams studied by detailed methods is shown in Table 1, "Summary of Discharges."

TABLE 1 - SUMMARY OF DISCHARGES

FLOODING SOURCE AND LOCATION	DRAINAGE AREA (sq. miles)	PEAK DISCHARGE (cfs) 100-YEAR
LEHIGH RIVER		
Above confluence with Spruce Run	39.3	11,880
Above confluence with Ash Creek	33.3	10,400
At outflow of West End Pond	15.8	5,730
MEADOW BROOK		
At confluence with Tamarack Creek	3.24	1,610

3.2 Hydraulic Analyses

Analyses of the hydraulic characteristics of flooding from the sources studied were carried out to provide estimates of the elevations of floods of the selected recurrence intervals.

Cross sections were field surveyed and located at close intervals above and below bridges and culverts in order to compute the significant backwater effects of these structures. All bridges, dams, and culverts in the community were field surveyed to obtain elevation data and structural geometry.

Locations of selected cross sections used in the hydraulic analyses are shown on the Flood Profiles (Exhibit 1) and the Flood Insurance Rate Map (Exhibit 2) where applicable.

Water-surface elevations of floods of the selected recurrence interval for the Lehigh River, from the downstream corporate limits to a point approximately 750 feet above the bridge on road T-303, were computed by modeling channel and bridge hydraulics with the USGS WSPRO step-backwater computer program (References 3 and 4). For the remaining portion of the Lehigh River and for Meadow Brook, normal depths of flooding for the 100-year recurrence interval were estimated from the regional relationship between drainage area and flood depth prepared by the USGS (Reference 5). This relationship was developed by means of regional regression analyses of basin areas and 100-year within-channel depths observed at stream gages.

Channel roughness factors (Manning's "n") used in the hydraulic computations were assigned on the basis of engineering judgment and field inspection of the floodplain areas. The channel "n" values for the streams studied by detailed methods ranged from 0.035 to 0.037, and the overbank "n" values ranged from 0.048 to 0.065.

The hydraulic analyses for this study were based on unobstructed flow. The flood elevations shown on the profiles are thus considered valid only if hydraulic structures remain unobstructed, operate properly, and do not fail.

All elevations are referenced to the National Geodetic Vertical Datum of 1929 (NGVD). Elevation reference marks used in this study are shown on the maps; the descriptions of the marks are presented in Elevation Reference Marks (Exhibit 3).

4.0 FLOODPLAIN MANAGEMENT APPLICATIONS

The NFIP encourages State and local governments to adopt sound floodplain management programs. Therefore, each Flood Insurance Study provides 100-year flood elevations and delineations of the 100-year floodplain boundaries to assist communities in developing floodplain management measures.

4.1 Floodplain Boundaries

To provide a national standard without regional discrimination, the 1 percent annual chance (100-year) flood has been adopted by FEMA as the base flood for floodplain management purposes. For the streams studied in detail, the 100-year floodplain boundaries have been

delineated using the flood elevations determined at each cross section. Between cross sections, the boundaries were interpolated using topographic maps at a scale of 1:24,000 with a contour interval of 20 feet (Reference 6).

For the streams studied by approximate methods, the 100-year floodplain boundaries were delineated using the Flood Hazard Boundary Map for the Township of Clifton (Reference 7).

The 100-year floodplain boundaries are shown on the Flood Insurance Rate Map (Exhibit 2). On this map, the 100-year floodplain boundary corresponds to the boundary of the areas of special flood hazards (Zones A and AE). Small areas within the floodplain boundaries may lie above the flood elevations but cannot be shown due to limitations of the map scale and/or lack of detailed topographic data.

4.2 Floodways

Encroachment on floodplains, such as structures and fill, reduces flood-carrying capacity, increases flood heights and velocities, and increases flood hazards in areas beyond the encroachment itself. One aspect of floodplain management involves balancing the economic gain from floodplain development against the resulting increase in flood hazard. For purposes of the National Flood Insurance Program, a floodway is used as a tool to assist local communities in this aspect of floodplain management. Under this concept, the area of the 100-year floodplain is divided into a floodway and a floodway fringe. The floodway is the channel of a stream, plus any adjacent floodplain areas, that must be kept free of encroachment so that the 100-year flood can be carried without substantial increases in flood heights. Minimum federal standards limit such increases to 1.0 foot, provided that hazardous velocities are not produced.

The area between the floodway and 100-year floodplain boundaries is termed the floodway fringe. The floodway fringe encompasses the portion of the floodplain that could be completely obstructed without increasing the water-surface elevation of the 100-year flood by more than 1.0 foot at any point. Typical relationships between the floodway and the floodway fringe and their significance to floodplain development are shown in Figure 2.

No floodways were calculated as part of this study.

5.0 INSURANCE APPLICATIONS

For flood insurance rating purposes, flood insurance zone designations are assigned to a community based on the results of the engineering analyses. The zones are as follows:


100 YEAR FLOOD PLAIN
FLOODWAY FRINGE
FLOODWAY
FLOODWAY FRINGE
STREAM CHANNEL
FLOOD ELEVATION WHEN CONFINED WITHIN FLOODWAY
ENCROACHMENT
ENCROACHMENT
C
D
SURCHARGE*
A
B
AREA OF FLOOD PLAIN THAT COULD BE USED FOR DEVELOPMENT BY RAISING GROUND
FLOOD ELEVATION BEFORE ENCROACHMENT ON FLOOD PLAIN
LINE A - B IS THE FLOOD ELEVATION BEFORE ENCROACHMENT
LINE C - D IS THE FLOOD ELEVATION AFTER ENCROACHMENT
*SURCHARGE NOT TO EXCEED 1.0 FOOT (FEMA REQUIREMENT) OR LESSER AMOUNT IF SPECIFIED BY STATE

FLOODWAY SCHEMATIC Figure 2

Zone A

Zone A is the flood insurance rate zone that corresponds to the 100-year floodplains that are determined in the Flood Insurance Study by approximate methods. Because detailed hydraulic analyses are not performed for such areas, no base flood elevations or depths are shown within this zone.

Zone AE

Zone AE is the flood insurance rate zone that corresponds to the 100-year floodplains that are determined in the Flood Insurance Study by detailed methods. In most instances, whole-foot base flood elevations derived from the detailed hydraulic analyses are shown at selected intervals within this zone.

Zone AH

Zone AH is the flood insurance rate zone that corresponds to the areas of 100-year shallow flooding (usually areas of ponding) where average depths are between 1 and 3 feet. Whole-foot base flood elevations derived from the detailed hydraulic analyses are shown at selected intervals within this zone.

Zone AO

Zone AO is the flood insurance rate zone that corresponds to the areas of 100-year shallow flooding (usually sheet flow on sloping terrain) where average depths are between 1 and 3 feet. Average whole-depths derived from the detailed hydraulic analyses are shown within this zone.

Zone A99

Zone A99 is the flood insurance rate zone that corresponds to areas of the 100-year floodplain that will be protected by a Federal flood protection system where construction has reached specified statutory milestones. No base flood elevations or depths are shown within this zone.

Zone V

Zone V is the flood insurance rate zone that corresponds to the 100-year coastal floodplains that have additional hazards associated with storm waves. Because approximate hydraulic analyses are performed for such areas, no base flood elevations are shown within this zone.

Zone VE

Zone VE is the flood insurance rate zone that corresponds to the 100-year coastal floodplains that have additional hazards associated with storm waves. Whole-foot base flood elevations derived from the detailed hydraulic analyses are shown at selected intervals within this zone.

Zone X

Zone X is the flood insurance rate zone that corresponds to areas outside the 500-year floodplain, areas within the 500-year floodplain, and to areas of 100-year flooding where average depths are less than 1 foot, areas of 100-year flooding where the contributing drainage area is less than 1 square mile, and areas protected from the 100-year flood by levees. No base flood elevations or depths are shown within this zone.

Zone D

Zone D is the flood insurance rate zone that corresponds to unstudied areas where flood hazards are undetermined, but possible.

6.0 FLOOD INSURANCE RATE MAP

The Flood Insurance Rate Map is designed for flood insurance and floodplain management applications.

For flood insurance applications, the map designates flood insurance rate zones as described in Section 5.0 and, in the 100-year floodplains that were studied by detailed methods, shows selected whole-foot base flood elevations or average depths. Insurance agents use the zones and base flood elevations in conjunction with information on structures and their contents to assign premium rates for flood insurance policies.

For floodplain management applications, the map shows by tints, screens, and symbols, the 100-year floodplain. The locations of selected cross sections used in the hydraulic analyses are shown where applicable.

7.0 OTHER STUDIES

A Flood Insurance Study has been prepared for the Township of Spring Brook (Reference 8). The results of this study are in exact agreement with the results of that study.

A Flood Insurance Study has been prepared for the Township of Covington (Reference 9). Because of the differences in methodologies used to delineate approximate floodplain boundaries, discrepancies exist between this study and that study.

Flood Insurance Studies have been prepared for the Townships of Lehigh and Coolbaugh (References 2 and 10). Because they are based on more detailed analyses, the results of this study are not in exact agreement with the results of those studies.

Due to its more detailed nature, this study supersedes the Flood Hazard Boundary Map for the Township of Clifton (Reference 7).

8.0 LOCATION OF DATA

Information concerning the pertinent data used in preparation of this study can be obtained by contacting FEMA, the Natural and Technological Hazards Division, Liberty Square Building (Second Floor), 105 South Seventh Street, Philadelphia, Pennsylvania 19106.

9.0 BIBLIOGRAPHY AND REFERENCES

1. U. S. Department of the Interior, Geological Survey, Office of Water Data Collection, Interagency Advisory Committee on Water Data, "Guidelines for Determining Flood Flow Frequency," Bulletin 17B, Reston, Virginia, Revised September 1981.

2. Federal Emergency Management Agency, Federal Insurance Administration, Flood Insurance Study, Township of Lehigh, Lackawanna County, Pennsylvania, Washington, D. C., June 15, 1981.

3. U. S. Federal Highway Administration, Report FHWA/RD-86/108, Bridge Waterways Analysis Model/Research Report by J. O. Shearman, W. H. Kirby, and V. R. Schneider, Springfield, Virginia, 1985.

4. National Technical Information Service, Bridge Waterways Analysis Model/User's Instructions by J. O. Shearman, W. H. Kirby, and V. R. Schneider, Springfield, Virginia, 1985.

5. U. S. Department of the Interior, Geological Survey, Water-Resources Investigations 86-4195, Technique for Estimating Depths of 100-year Floods in Pennsylvania by H. N. Flippo, Jr., Harrisburg, Pennsylvania, 1986.

6. U. S. Department of the Interior, Geological Survey, 7.5-Minute Series Topographic Maps, Scale 1:24,000, Contour Interval 20 Feet: Moscow, Pennsylvania, 1946, Photorevised 1969 and 1976; Thornhurst, Pennsylvania, 1965, Photorevised 1973; and Tobyhanna, Pennsylvania, 1965, Photorevised 1973.

7. U. S. Department of Housing and Urban Development, Federal Insurance Administration, Flood Hazard Boundary Map, Township of Clifton, Lackawanna County, Pennsylvania, February 27, 1981.

8. Federal Emergency Management Agency, Flood Insurance Study, Township of Spring Brook, Lackawanna County, Pennsylvania, Washington, D. C., January 20, 1982.

9. Federal Emergency Management Agency, Flood Insurance Study, Township of Covington, Lackawanna County, Pennsylvania, Washington, D. C., September 1, 1986.

10. Federal Emergency Management Agency, Flood Insurance Study, Township of Coolbaugh, Monroe County, Pennsylvania, Washington, D. C., November 4, 1988.

EXHIBIT 3 - ELEVATION REFERENCE MARKS

Reference Mark	FIRM Panel	Elevation (Feet NGVD)	Description of Location
RM 1	05	1,570.40	Standard disk, stamped 31 HL2 1964 RESET 1971, in top of southeast wing wall of bridge over Spruce Run; approximately 11 feet south, 6 feet east, and 1.6 feet lower than centerline of LR 2013.
RM 2	05	1,605.84	Chiseled square on top of east side of south guardrail of LR 2013 bridge over Ash Creek.
RM 3	10	1,874.06	Chiseled square on top of south side of concrete buttress of dam at outlet of West End Pond.
RM 4	10	1,807.40	PDH tablet, stamped 67 HLZ 1964 USGS, on southeast wing wall of LR 2013 bridge over Meadow Brook.


CORPORATE LIMITS
ACCESS ROAD
1610
1600
1590
1580
1570
1560
1550
ELEVATION IN FEET (NGVD)
0
5
10
15
20
25
30
35
40
45
50
55
60
65
STREAM DISTANCE IN HUNDREDS OF FEET ABOVE CORPORATE LIMITS
A
B
C
D
100 YEAR FLOOD
STREAM BED
CROSS SECTION LOCATION
FLOOD PROFILES
LEHIGH RIVER
FEDERAL EMERGENCY MANAGEMENT AGENCY
TOWNSHIP OF CLIFTON, PA
(LACKAWANNA CO.)
01P

T-303

LIMIT OF DETAILED STUDY

ELEVATION IN FEET (NGVD)

1620
1610
1600
1590

65 70 75 80 85 90 95 100 105

STREAM DISTANCE IN HUNDREDS OF FEET ABOVE CORPORATE LIMITS

E F G

100 YEAR FLOOD

STREAM BED

CROSS SECTION LOCATION

FLOOD PROFILES

LEHIGH RIVER

FEDERAL EMERGENCY MANAGEMENT AGENCY

TOWNSHIP OF CLIFTON, PA

(LACKAWANNA CO.)

02P



03P

FEDERAL EMERGENCY MANAGEMENT AGENCY

TOWNSHIP OF CLIFTON, PA
(LACKAWANNA CO.)

FLOOD PROFILES

LEHIGH RIVER

ELEVATION IN FEET (NGVD)

1810
1800
1790
1780

CONFLUENCE WITH TAMARACK CREEK

LIMIT OF DETAILED STUDY

LIMIT OF DETAILED STUDY

L.R. 2013 AND DAM

1810
1800
1790
1780

0 5 10 15 20 25 30

STREAM DISTANCE IN HUNDREDS OF FEET ABOVE CONFLUENCE WITH TAMARACK CREEK

100 YEAR FLOOD

STREAM BED

CROSS SECTION LOCATION

FLOOD PROFILES

MEADOW BROOK

FEDERAL EMERGENCY MANAGEMENT AGENCY

TOWNSHIP OF CLIFTON, PA
(LACKAWANNA CO.)

04P